

GEE LOK valves pipes and fittings trading llc.

www.geelok.com

Welcome to **GEE LOK** values PIPES AND FITTINGS TRADING LLC., your trusted partner in UAE for top-quality instrumentation fittings and values. With a vast experience and a commitment to excellence, we are your one-stop solution for all your precision engineering needs. Discover the perfect products that ensure reliable and efficient performance in your industrial operations.

Premium Quality: We prioritize quality and durability in every product we offer. Our instrumentation fittings and valves are manufactured to the highest industry standards, ensuring exceptional performance and longevity.

Wide Product Range: We understand the diverse requirements of different industries. Our extensive product range includes a variety of fittings and valves, ensuring you find the perfect solution for your specific needs.

Customised Solutions: We believe in catering to our clients' unique requirements. Our team of experts are ready to collaborate with you to design and deliver customised instrumentation fittings and valves tailored to your application, ensuring optimal performance and efficiency.

Prompt Delivery: We understand the importance of timely delivery for your projects. With our efficient logistics network, we ensure your orders are processed and delivered promptly, helping you stay on schedule and minimize downtime.

Competitive Pricing: We strive to provide excellent value for your investment. Our competitive pricing ensures you receive topquality products without compromising your budget.

Our Product Range:

1. Instrumentation Fittings: We offer a comprehensive range of instrumentation fittings, including compression fittings, tube fittings, pipe fittings, and flare fittings. These fittings are designed to provide leak-free connections and ensure efficient fluid or gas transmission.

2. Instrumentation Valves: Our selection of instrumentation valves includes ball valves, needle valves, check valves, SBBs (single block & bleed) valve, DBBs (double block & bleed) valve and manifold valves. These valves are engineered to control flow, pressure, and direction, enabling precise control and safety in your operations.

3. Tube and Tubing: We provide high-quality tubes and tubing made from various materials such as stainless steel, carbon steel, and copper. Our tubes are available in different sizes and configurations to suit your specific requirements.

Industries We Serve: Oil and Gas, Petrochemicals and Fertilizers, Power Generation, Chemical and Pharmaceutical, Water and Wastewater Treatment. etc.

Please feel free to contact us today to discuss your requirements and benefit from our expertise in precision engineering. Let us be your trusted partner in UAE for all your instrumentation needs. Together, we can achieve excellence in performance, efficiency, and reliability.

We are authorized distributor of **BAL VALVES AND FITTINGS (INDIA) PVT. LTD.**



TUBE FITTINGS

- Compression type Double ferrule tube fittings
- The Double ferrule optimize sealing and tube gripping function to provide excellent leak-tight connection
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Sizes: 1/8"~1" pipe thread & 3mm~25mm 0.D.
- Material Traceability







PIPE FITTINGS

- Used for process control and instrumentation Connections
- Precision machined from forgings for shaped fittings and from bar stock for straight connectors
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Male threads are capped for protection
- Sizes: 1/8"~2" pipe.
- Material Traceability













315

の日日



- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature: up to 464°F (240°C) with PTFE packing up to 842°F (450°C) with Graphite packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Adjustable packing to extend service life.
- Size: 1/4 ~2" pipe thread 3~25mm OD, 1/8"~1" OD
- Leak tight performances testing for every valve with nitrogen/ air at the maximum working pressure
- Panel Mountable(optional)
- Low Operating Torque
- Forged Body Straight & angle pattern.
- 100% factory tested
- Material Traceability



















- **MANIFOLD VALVES**
- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature: -65°F (-54°C) to 464°F (240°C) with PTFE packing -65°F (-54°C) to 842°F (450°C) with Graphite packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Available with Pipe to Pipe, Pipe to Flange, Flange to Flange, Remote, Remote Mounting base
- Vent, Direct and Integral Mounting
- Standard Non-rotating trim
- Low Operating Torque
- One piece high strength bar stock and forged body
- 100% factory tested
- Material Traceability




















- Maximum Working Pressure up to 6000 psi (414 bar)
- Working Temperature: -65°F (-54°C) to 464°F (240°C) with PTFE packing -65°F (-54°C) to 842°F (450°C) with Graphite packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Available with Pipe to Pipe, Pipe to Flange, Flange to Flange, Remote, Remote Mounting base
- Vent, Direct and Integral Mounting
- Standard Non-rotating trim
- Low Operating Torque
- One piece high strength bar stock and forged body.
- 100% factory tested
- Material Traceability



- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature: -10°F (-23°C) to 392°F (200°C) with Viton 'O' ring
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Size: 1/8 ~2" pipe thread 3~25mm OD, 1/8"~1" OD
- Instant shut off in upstream Condition.
- Compact Design
- 100% factory tested
- Material Traceability













BALL VALVES

- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature: up to 212°F (100°C) with Delrin packing up to 464°F (240°C) with PTFE packing up to 842°F (450°C) with PEEK packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Size: 1/4 ~2" pipe thread, 3~25mm OD & 1/8"~1" OD
- Leak tight performances testing for every valve with nitrogen/ air at the maximum working pressure
- 100% factory tested
- Panel Mountable(optional)
- Low Operating Torque
- Floating ball design for positive sealing
- Material Traceability
- Compact design
- Single piece design and Three piece design
- 2 Way, 3 Way & 5 Way









RELIEF VALVES

- Maximum Working Pressure up to 6000 psi (414 bar)
- Working Temperature from -22°F (-30°C) to 392°F (200°C)
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Size: 1/4" ~1" pipe thread 6mm ~25mm 0D, 1/4"~1" 0D
- Set Pressure from 10 to 6000 psi (3.4 to 414 bar)
- Multiple springs for a wide range of set pressure
- Easy external pressure adjustment
- Label identifies the set pressure range
- 100% factory tested
- Material Traceability



FORGED FITTINGS



Pressure Regulator are available in SS316L

Available in SS304L/SS316L, Monel,

Hastelloy, Inconel & Duplex

- Available with a variety of porting and material options.
- Piston sensed design in safe and reliable
- Maximum working pressure up to 6000 psi (414 bar)
- Adjustable stop limits maximum outlet pressure
- Low operating torque
- 100% factory tested
- Material traceability
- Back pressure, Single stage & Double Stage.





- Used for process control and Hydraulic Connections
- Machined from forgings for shaped fittings and from bar stock for straight Hydraulic connectors
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Male threads are capped for protection
- Sizes: 1/8"~2" pipe.
- Material Traceability



- **37° FLAIR FITTINGS**
- Machined from forgings for shaped fittings and from bar stock for straight Connectors
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Male threads are capped for protection
- Sizes: 1/8"~2" pipe.
- Material Traceability







- HOSE FITTINGS
 - Used for process control and Hydraulic Connections
 - Bar stock for straight & Bend Hydraulic connectors
 - Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
 - Variety of thread type: NPT, BSPT, ISO, SAE
 - Male threads are capped for protection
 - Sizes: 1/8"~2" pipe.
 - Material Traceability



CONDENSATE POTS

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Small thin design & light weight design allows you to combine with other valves in series for safe shutoff.
- End connection NPT, SW as per ANSI B2.1 & B16.11
- Wall thickness schedule 40, 80 & 160
- Maximum working pressure up to 10000 psi (689 bar)
- Size ranging from ½" to 2"
- 100% factory tested
- Material traceability
- 2 Port, 4 Port, 6 Port, 8 Port, 10 Port
- 100% Radiography of pipe joints

GLOBAL



AIR HEADERS

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of end connections -Threaded, Flanged, Socket Weld, will be as per ANSI B16.11
- 100% Radiography of pipe joints.
- Fabrication as per ASME SEC VIII DIV 1 ED
- Material traceability.



- *THERMOWELLS*
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Various range Threaded, Flanged, Socket weld, Tapered & Straight
- Instrument connection ½" NPT / NPSM.
- Insertion length (U) up to 28"
- One piece construction
- Other thread sizes available upon request

Material traceability.

PRESSURE GAUGE & ACCESSORIES





 Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex



Authorised Distributer of:





HEAD OFFICE DUBAI - UAE

GEE LOK Valves Pipes & Fittings Trading LLC. Shop No-4, Al Nakheel Road, Deira, Dubai, UAE. Tel: +971 4 458 1391 Cell: +971-52-4534877 E-Mail: info@geelok.com Website: www.geelok.com

ABU DHABI - UAE

GEE LOK Valves Pipes & Fittings Trading - Branch of Abu Dhabi 1 7, Mussafah-9, Abu Dhabi, UAE Tel: +971 2 582 4227 Cell: +971-52-4534877 E-Mail: sales@geelok.com

AJMAN - UAE

GEE LOK VALVES & FITTINGS - F.Z.E. Warehouse No- 11-40, Ajman Free Zone, Gate no - 1 Ajman, UAE E-Mail: sales1@geelok.com

IMPORTANT NOTICE:

- The product data in this catalogue was obtained under specific test conditions that may vary substantially from actual site conditions and / or customer needs.
- Purchasers or other end users of our products should rely solely on their system design engineers while selecting products for a particular system, and when determining the suitability of any system in which our product is to be installed.
- The company shall bear no liability regarding product selection criteria or decisions, nor shall be liable (including direct, special or consequential damages including, but not limited to, lost profits or income) in regard to any product which has been damaged by misuse, improper handling or accident, or as a result of service or modification by anyone other than an authorized employee or agent of our company, or being subjected to use under conditions, or combinations of conditions, that are not compatible with that particular product.